



Umuziwabantu Municipality
Tel No: 0394333500/Fax 0394331208

RE-ADVERT
SUPPLY, DELIVER AND INSTALLATION OF RFID
SECURITY GATE
NOTICE NO.16/2019-2020

REQUEST FOR FORMAL WRITTEN PRICE QUOTATIONS

(Over R30 000.00 up to a transaction value of R200 000.00 VAT included)

Kindly furnish me with a written quotation for the supply of the goods/services
As detailed in the enclosed schedule.

The quotation must be submitted on the letterhead of your business and can be
delivered by hand not later than

27/08/2019 @ 11H:00

The following conditions will apply:

- Price(s) quoted must be valid for at least thirty (30) days of your offer.
- Price(s) quoted must be firm and must be inclusive of VAT.
- Firm delivery period must be stated
- BBEE Certificate will be advantageous
- MBD 1
- MBD 4
- MBD 9
- Two Purchase orders / two reference letters signed by Supply Chain Manager/ Chief Financial Officer
- A successful bidder will be required to register on the Central supplier database.

PREFERENTIAL PROCUREMENT POLICY FRAMEWORK ACT (PPPFA) POINTS WILL BE ALLOCATED AS FOLLOWS:

80 – Price, 20 – BEE Contribution Level Status


NB: All quotations must be deposited on a quotation box at the finance department next to Russells furniture shop

NB: Bids will be rejected if any municipal rates and taxes or municipal service charge owed by that bidder or any of its directors to the Umuziwabantu Municipality or to any other municipality or municipal entity, are in arrears for more than three months

Failure to comply with these conditions will invalidate your offer


QUANTITY	DESCRIPTION		
	SUPPLY, DELIVER AND INSTALLATION OF RFID SECURITY GATE AS PE THE ATTACHED SPECIFICATION OR SIMILAR		
	TO BE INTALLED IN HARDING LIBRARY		

NB: ENQUIRIES CAN BE DIRECTED TO MR S. ZUNGU ON 039 433 3500/22 DURING OFFICE HOURS



**MR T.W. GUMEDE
MUNICIPAL MANAGER**

**DELIVERY ADDRESS:
UMUZIWABANTU MUNICIPALITY
LOT 10 MURCHISON STREET
FINANCE OFFICES
HARDING
4680**

UMUZIWABANTU MUNICIPALITY	
PRIVATE BAG X1023 HARDING 4680	
CHECKED BY SCM MANAGER:	
SIGNATURE	: 
DATE	: 20/08/2019.

Specifications : bibliotheca RFID gate™

Dimensions (w x d x h):	Millimetres: 73 (Max at base) x 680 x 1,780 (± 3) Inches: 2.87 (Max at base) x 26.77 x 70.08 (± 0.1)
Weight (per gate):	Kilograms: 28 Pounds: 62
Material:	Transparent panel, "aluminium like RAL9006" ABS with light texture base Enclosure Rating: IP 41
Power:	Supply voltage: 24 V ac Power consumption: 32VA
Data:	Ethernet (TCP/IP)
Performance:	Reads* up to 8 tags per second. Optimal coverage is achieved within 43 inches / 1,100 mm of separation. Coverage up to 47 inches / 1,200 mm can be achieved with certain tags. *Detection of items cannot be 100% guaranteed in any gate setup due to a range of factors. Detection range and rates will always be reduced for CD and DVD media that contains metallic elements. Libraries wishing to get as close to 100% detection as possible should work with the project team, but should expect distance between gates to be reduced.
RFID specification:	Operating frequency: 13,56 MHz, Max. Transmitting power: 8 W Supported tags types: ISO 15693, ISO 18000-3-A, (Infineon my-d, NXP I-Code, SLI, SL1x, SL1x2)
Alarm:	Multi-colour*, customer selectable LED lights Variable alarm pattern and adjustable volume Highly visible integrated digital display to monitor alarm counts, ingoing and outgoing library user traffic, and diagnostics *Available colours: red, cyan, magenta, blue, green, yellow, white
Standards compliance:	CE, RCM, ETSI, FCC, IC, ADA, DDA, UL and CSA
Temperature range:	Operating: -25 °C to +50 °C/Storage: -25 °C to +70 °C
Configurations:	Standard configuration can support up to 7 panels to provide total coverage of 7.7m. Additional panels can be added by synchronising readers.
Installation:	Multiple installation options including direct attachment to the floor with either in floor wiring or a wire way and a baseplate option.
Software:	Software is not required for the RFID gate to operate, however, when used in conjunction with our staffConnect™ gate software, enhanced reporting is available.
Additional features:	Integrated bi-directional people counter, standby mode to minimise power consumption.

Specifications : bibliotheca RFID workstation™ shielded

Dimensions (w x d x h):	350 mm x 280 mm x 15 mm
Shield:	fully shielded
Weight:	Kilograms 1.5 kg Pounds: 3.825 lbs
Power:	RFID reader connects to PC via USB; it is supplied with a localised plug-in supply (110V ac/60Hz or 240V ac/50Hz). The RF power output is 1.2 Watt and the workstation™ shielded conforms to CE and FCC.
Membership cards supported:	Barcode and RFID-enabled membership cards.
Software:	Our staffConnect™ circ software will need to be installed on your existing PC, running Microsoft® Windows (XP SP3 or W7 32/64). Connection to the LMS/ILS is only required for some of the functionalities.
Options:	A receipt printer and/or barcode scanner can be added to any workstation™.